



Model: **RH2-SPACE**
120/208/240V-1-50/60Hz

Improve Comfort and Protect Investments

Features:

- Quiet drain valve for ultra-quiet operation
- Pure, clean, sterile steam humidification
- Self-generating electrode type steam humidifier producing atmospheric steam inside a plastic cylinder without the use of immersion type electric heating elements
- Easy maintenance using disposable cylinders that last one to two years depending on water
- Auto-adaptive technology adapts to changing water conditions
- Automatic fill and drain cycles
- Wall mounted for direct room distribution
- Improves comfort and health
- Reduces static electricity
- Optional Temperature Sensor (duct or outdoor mount) reads outdoor temp and resets humidity control set-point to prevent condensation on windows
- 5-Year Warranty

Studies show that correct interior humidity levels minimize the spread of bacteria and viruses, avoiding the problems associated with dry throats and nasal passages during the winter months. Wood and upholstered furniture, drapes, carpets and even fabrics around your home deteriorate more rapidly when conditions are too dry or too wet.

RH2+ electrode steam humidifiers remove calcium and minerals from the water supply to ensure that only clean, pure steam is added to your indoor air, making the air in your home healthier to breathe. Scale and mineral sediment is collected in the cylinders which are easily changed and discarded. Cylinder replacement requires no special tools and can be done in a few minutes. A light on the unit indicates when the cylinder needs replacement.

Installation requires only a potable water supply, water drainage and 110-240V power. The RH2+ Space model features a quiet drain valve and is wall mounted and contains an integral blower to put atmospheric steam into the living space.

SPECIFICATIONS: RH2-SPACE

Wiring Connection	Hardwired
Rated Current	12.7 Amp
Max. Ext. Protection	20 Amp
Dimensions in (cm)	21.4 (54.4) H x 11.4 (29.0) W x 6.9 (17.4) D
Controls	On/Off or Modulating
Weight lbs (kg)	21 (9.5)
Steam Distribution	Built-in Blower



VOLTS	CAPACITY/HR LBS (KG)	OUTPUT/HR GAL (LTRS)	OUTPUT/DAY GAL (LTRS)	KW	NET WEIGHT LBS (KG)	FULL WEIGHT LBS (KG)
110-120	4 (1.8)	0.5 (1.8)	12 (45)	1.5	16 (7.5)	22 (10.0)
208	6.9 (3.1)	0.8 (3.1)	19.2 (73)	2.6	16 (7.5)	22 (10.0)
220-240	8 (3.6)	1.0 (3.6)	24 (91)	3.0	16 (7.5)	22 (10.0)

PART NUMBERS & ACCESSORIES		
PART #	DESCRIPTION	FIGURE
RH2-SPACE	RH2+ Steam Humidifier Space Unit	1
RH2-HWM	RH2+ Wall Mount Humidistat	2
RH2-TSOM	Temperature Sensor Outdoor Mount	3
RH2-TSDM	Temperature Sensor Duct Mount	3
RH2-RC	Replacement Cylinder 202 Series	4



FIG. 1



FIG. 2



FIG. 3



FIG. 4